

Powerflow 8/5 Single Discharge

The GP 8/5 is a compact and lightweight portable fire pump with a rated performance of 800l/min at 5 bar of pressure with a 3 metre lift.. Powered by 18HP Briggs and Stratton engine, this pump uses a single discharge valve and is available with exhaust priming system, electric or manual starting.

Features

- Ultra compact and lightweight – frees up locker space for other equipment
- Up to 12% smaller and 10% lighter than comparable pumps
- A range of flows to suit differing needs
- Priming - exhaust gas ejection or hand priming versions (single discharge only)



Specifications

Certification(s)	
Weight	154 lbs (dry)
Length	22 inches (555 mm)
Width	19.3 inches (490 mm)
Height	23 inches (584 mm)
Flow (GPM)	308 gpm @ 43.5 psi
Flow (LPM)	1400 l/min @ 3bar
Rated Output LPM	800 l/min @ 3 bar
Rated Output GPM	176.2 gpm @ 43.5 psi
Maximum flow - High pressure	1420 l/min
Maximum outlet pressure bar	8.2 bar
Maximum outlet pressure psi	119 psi
NFPA 1906 or EN Rated Capacity	800 l/min @ 5 bar
Application Solutions Portables	Transportable / Self Contained
Performance Application Type	Low Pressure, Medium Flow
Dimensions	Extra Small
Priming Option	Manual, Exhaust,

