



PowerFlow HPX200-B23

Product code: 545-5161-30-0

Applications: Fire OEMs, Firefighting - Wildland Forestry

Overview

You want flexibility and performance. High quality is your minimum standard. That's why the Hale Attack Firefighting pump range are designed to be tough and perform well at higher or lower pressures. Hale has over 100 years' experience making fire pumps so you can be sure your Hale pump will deliver performance when you need it.

Features

- Flows ranging from 90 GPM @ 150 PSI to 250 GPM @ 30 PSI
- Ultra-reliable Briggs & Stratton 23-HP 4-cycle V-Twin gasoline engine
- Electric start with recoil backup
- Anodized aluminum alloy pump head and body
- Pump head and body coupled together with stainless steel band clamp for easy serviceability
- Bronze impeller and renewable wear rings
- Self-adjusting mechanical seal
- Exhaust gas venturi priming
- 3.0" NPT / 4.0" Victaulic suction connection; 2.5" NPT discharge

Technical details & documents

Specification

Application Solutions Portables	Slip-on
Certifications	CE, EPA Approved, NFPA 1906
Brand	Hale Products
Application Solutions	Fire OEMs, Firefighting - Wildland Forestry
Performance Application Type	Medium Pressure, Medium Flow
Product or Spare Part	Finished Good
Priming Option	Manual, Exhaust, Electric
Weight (Imperial)	145 lbs
Weight (Metric) kg	66 kg



Width (English)	18 inches
Width (Metric)	457 mm
NFPA 1960 2024 Compliant	No
Dimensions	Extra Small
Height (English)	20.25 inches
Height (Metric)	514 mm
Length (English)	22 inches
Length (Metric)	559 mm
Engine Power	23.00 HP

