



PowerFlow HPX75-B23

Product code: 545-075X0-B23

Applications: Fire OEMs, Firefighting - Wildland Forestry

Overview

You deserve fire pumps that you can depend on, first time, every time. That's why the Hale high pressure pump range are designed to be tough and dependable performers. Hale has over 100 years' experience making fire pumps so you can be sure your Hale pump will deliver performance when you need it.

Features

- Flows ranging from 15 GPM @ 380 PSI to 135 GPM @ 80 PSI
- Ultra-reliable Briggs & Stratton 23-HP 4-cycle V-Twin gasoline engine
- Electric start with recoil backup
- Anodized aluminum alloy pump head and body
- Pump head and body coupled together with stainless steel band clamp for easy serviceability
- Bronze impeller and renewable wear ring
- Self-adjusting mechanical seal
- Exhaust gas venturi priming
- 2.0" NPT suction connection; 1.5" NPT discharge

Technical details & documents

Specification



Certifications	CE, NFPA 1906
Brand	Hale Products
Application Solutions	Fire OEMs, Firefighting - Wildland Forestry
Product or Spare Part	Finished Good
Weight (Imperial)	157 lbs
Weight (Metric) kg	71 kg
Width (English)	18 inches
Width (Metric)	457 mm
NFPA 1960 2024 Compliant	No
Height (English)	20 inches
Height (Metric)	508 mm
Length (English)	21 inches
Length (Metric)	533 mm
Engine Power	0.00 HP

